



Indorama Ventures Fibers Germany GmbH

Trademark Service

Max-Fischer-Str. 11

86399 Bobingen, Germany

trademarkservice.IVFG@de.indorama.net

Tel. +49 8234 9688 1673

www.indoramaventures.com



## Approval of the Trademark Trevira CS®

MARIO SIRTORI S.P.A  
via Papa Giovanni XXIII n 10  
23845 Costa Masnaga  
Italy

<b>Application No.:</b>	<b>230601.1</b>
<b>Date of issue:</b>	08.10.2025
<b>Valid until:</b>	20.07.2028
<b>Article name:</b>	SHIRLEY CS
<b>Color:</b>	white
<b>End use:</b>	Drapes Curtains Upholstery fabrics Bedding
<b>Square weight (g/m²):</b>	520
According to customer specification	
<b>Composition of the raw materials:</b>	100% Polyester
<b>Composition of the fabric:</b>	100% Trevira CS

The article SHIRLEY CS has been tested under the trademark application no. 230601 and is granted approval for the trademark Trevira CS® for interior use.

This article was tested according to DIN 4102 part 1, 6.2 and thus also meets the requirements for fire class DIN 4102-B1.

The article meets the requirements for class 1 according to EN 13773.

The article qualifies for class B-s1, d0 according to the European Standard EN 13501-1. Trevira CS has been approved by the DIBt with the General Building Inspectorate Approval, Approval No. Z-56.25-3573 dd. 10 January 2024.

The article meets the requirements according to EN 1021-1 and -2:2014 in conjunction with polyurethan foams with a density of more than 30 kg/m³.

The article meets also the requirements for class 1 according to the Italian Standards UNI 8456 and UNI 8457.

**INDORAMA**  
VENTURES

Indispensable Chemistry



The article meets the requirements according to the Italian standard UNI 9175, class 1 IM in conjunction with suitable combustion modified foams.

The article meets also the requirements according to British Standard BS 5867 part 2 type C.

The article meets also the requirements according to British Standard BS 5852 ignition source 0 (cigarette), ignition source 1 (match) and ignition source (crib 5) in conjunction with suitable combustion modified foams (at least 50 kg/m<sup>3</sup>). Thus meets the classification according to BS 7176 "Medium Hazard".

The article can meet the requirements of class 1Y according to BS 476: Part 7: 1997 / Surface Spread of Flame.

The article meets the requirements according to the North American standard NFPA 701: 2010 Test Method #1 (based on the Test Reports Govmark, New York No. 2-94779, 2-94780, 2-94781).

The article also meets the requirements for class I according to the North American standard NFPA 260 for upholstered furniture (based on the Test Reports no. 10-002-775 A + B dated 24.11.2010).

The article can meet the requirements according to California TB 117-2013, section 1 - cover fabric.

The article also meets the requirements according to the North American NFPA Life Safety Code 101, class A, Test Standard ASTM E84 Surface Burning Characteristics, Test Report No. 12-002-527, dated August 30, 2012.

Indorama Ventures Fibers Germany GmbH  
(This document is valid without signature.)

