

www.textilecomo.com

via Castelnuovo, 3 - 22100 Como Italia Pho +39 031 3312111/120 Fax: +39 0313312149 Amministrazione/Contabilità +39 031 3312102-154 P. IVA - C.F. 003900470133 Capitale sociale euro 600000,00 iv mailbox@textilecomo.com





LAB N° 0045 L

Test Report No.: 2006501-001

Date Test Report 02-nov-20

2006501 Acceptance:

Arrival date sample 29-ott-20 Start date test 29-ott-20 End date test

References:

02-nov-20

Sampling Mode: Sampling by Customer * Customer Code 05485

Dear:

MARIO SIRTORI SPA

via Papa Giovanni XXIII 10

23845 COSTA MASNAGA (LC) Italia

sig. Sergio Sala Crist Phone: +39 031 879632

CARNIVAL [C] Item:

[C] Declared Compostion: 40% Cotton - 22% Acrylic - 16% Viscose - 11% Wool - 11% Polyester

[C] End use: Furnishing [C] Typology: Fabric Return: No requested

Test Results

Test	Method	U.M.	Result
15066 UPHOLSTERY FURNITURE COMPONENTS: ASSESSMENT OF THE IGNITABILITY BY SMOULDERING CIGAR	UNI EN 1021-1:2014 ETTE		
Instrument: Small Test Rig			
Test carried out on			cover fabric
Pretreatment carried out			
sample wasn't submitted to any pretreatment	because it wasn't chemically treated with flame retardant		
Ignition source			source 0 (SMOULDERING CIGARETTE)
Materials of test assembly			·
Upholstery filling: fire retardant polyurethane Inner cover: - Outer cover: SEE ARTICLE DESCRIPTION	foam with a density of 35 kg/m ³		
TEST RESULT			SAMPLE PASSE THE TEST
Deviations from the method			none
Annex n.			1F
Details of the test results related to each spec	imen can be seen in the annex of this test report.		

The Results contained in this Report refer only to the Sample as received and do not imply an approval of the tested product by the Laboratory of the Centro Tessile Serico Sostenibile Srl. Unless otherwise specified, the side examined / straight of use is indicated by the Customer: this information can influence the results of the tests and therefore the Test Laboratory declines all responsibility.

This Report may not be reproduced in part, unless written permission of Centro Tessile Serico Sostenibile Srl Laboratory.

[C] = Information provided by the Customer, of which the Centro Tessile Serico Sostenibile Srl Laboratory declines all responsibility.

^{(*) =} The tests marked in this way are not accredited by Accredia



mailbox@textilecomo.com

via Castelnuovo, 3 - 22100 Como Italia Pho +39 031 3312111/120 Fax: +39 0313312149 Amministrazione/Contabilità +39 031 3312102-154 P. IVA - C.F. 003900470133 Capitale sociale euro 600000,00 iv





LAB N° 0045 L

Test Report No.:	2006501-001			
Test	Method	· ·	U.M.	Result
				The Laboratory Manager Fausto Albonico
		END OF REPORT		

The Results contained in this Report refer only to the Sample as received and do not imply an approval of the tested product by the Laboratory of the Centro Tessile Serico Sostenibile Srl. Unless otherwise specified, the side examined / straight of use is indicated by the Customer: this information can influence the results of the tests and therefore the Test Laboratory declines all responsibility.

^(*) = The tests marked in this way are not accredited by Accredia

This Report may not be reproduced in part, unless written permission of Centro Tessile Serico Sostenibile Srl Laboratory.

[[]C] = Information provided by the Customer, of which the Centro Tessile Serico Sostenibile Srl Laboratory declines all responsibility.







Tel +39 031 331211/120 Fax +39 031 3312180 Amministrazione/Contabilità +39 031 3312102-154 P.IVA - C.F. 02381270137 Capitale sociale euro 552.693,18 i.v. mailbox@textilecomo.com

www.textilecomo.com

Centro Tessile Serico Spa consortile Via Castelnuovo, 3 - 22100 Como, Italia





I AR Nº 0045 I

Annex n. 1F to test report n. 2006501-001

DETAILS OF TEST RESULTS

Test executed according to UNI EN 1021-1:2014 (EN 1021-1:2014)

Furniture

Assessment of the ignitability of upholstered furniture

Part 1: Ignition source: smouldering cigarette

Article description: CARNIVAL

Declared composition: 40% Cotton - 22% Acrylic - 16% Viscose - 11% Wool - 11% Polyester

Materials of test assembly:

Upholstery filling: fire-retardant polyurethane foam with a density of 35 kg/m³

Inner cover: -

Outer cover: see article description

Conditioning of test specimen: 23 ± 2 °C, 50 ± 5 % r.h.

Testing temperature and r.h.: 19°C, 55% r.h.

Sample pre-treatment: sample wasn't submitted to any pretreatment because it wasn't chemically treated

with flame retardant Date of test: 02.11.2020

SMOULDERING CRITERIA:	first cigarette	second cigarette	Third cigarette	Comments
Smouldering criteria:				
Unsafe escalating combustion	NO	NO	NO	-
Test assembly consumed	NO	NO	NO	-
Smoulders to extremities	NO	NO	NO	-
Smoulders through thickness	NO	NO	NO	-
Smoulders more than 1 h	NO	NO	NO	Time elapsed between placing the cigarette and extinguishing 1st 18 min (partial combustion) 2nd 27 min 3th 31 min
In final examination, presence of active smouldering	NO	NO	NO	-
Flaming criteria:				
Evidence of flames	NO	NO	NO	

YES = criteria observed

NO = criteria not observed

TEST RESULT: SAMPLE PASSES THE TEST - NON IGNITION

The above test results relate only to the ignitability of the combination of materials under the particular conditions of test. They are not intended as a means of assessing the full potential fire hazard of the material in use.

The probability that the observation criteria mentioned represent the true is equal to 95%.

The expanded uncertainty is calculated by multiplying the combined standard uncertainty for a coverage factor K = 2, which for a normal distribution leads to a confidence level of approximately 95%.



via Castelnuovo, 3 - 22100 Como Italia Pho +39 031 3312111/120 Fax: +39 0313312149 Amministrazione/Contabilità +39 031 3312102-154 P. IVA - C.F. 003900470133 Capitale sociale euro 600000,00 iv mailbox@textilecomo.com www.textilecomo.com



Customer Code 05485

MARIO SIRTORI SPA

Phone: +39 031 879632

via Papa Giovanni XXIII 10

23845 COSTA MASNAGA (LC) Italia

sig. Sergio Sala Crist

Dear:



LAB N° 0045 L

Test Report No.: 2006501-002

Date Test Report 02-nov-20

2006501 Acceptance:

Arrival date sample 29-ott-20 Start date test 29-ott-20

End date test 02-nov-20

References:

Sampling Mode:

CARNIVAL [C] Item:

Sampling by Customer *

[C] Declared Compostion: 40% Cotton - 22% Acrylic - 16% Viscose - 11% Wool - 11% Polyester

[C] End use: Furnishing [C] Typology: Fabric Return: No requested

Test Results

Test	Method	U.M.	Result
15076 UPHOLSTERY FURNITURE: ASSESSMENT OF THE IGNITABILITY BY MATCH FLAME	UNI EN 1021-2:2014		•
Instrument: Small Test Rig and burner			
Test carried out on			COVER FABRIC
Pretreatment carried out			
sample wasn't submitted to any pretreatment b	pecause it wasn't chemically treated with flame retardant		
Ignition source			source 1 (MATCH FLAME EQUIVALENT)
Materials of test assembly			·
Upholstery filling: fire retardant polyurethane for Inner cover: - Outer cover: SEE ARTICLE DESCRIPTION	pam with a density of 35 kg/m³		
TEST RESULT			SAMPLE PASSES THE TEST
Deviations from the method			none
Annex n.			1F
Details of the test results related to each specin	nen can be seen in the annex of this test report.		

(*) = The tests marked in this way are not accredited by Accredia

The Results contained in this Report refer only to the Sample as received and do not imply an approval of the tested product by the Laboratory of the Centro Tessile Serico Sostenibile Srl. Unless otherwise specified, the side examined / straight of use is indicated by the Customer: this information can influence the results of the tests and therefore the Test Laboratory declines all responsibility.

This Report may not be reproduced in part, unless written permission of Centro Tessile Serico Sostenibile Srl Laboratory.

[[]C] = Information provided by the Customer, of which the Centro Tessile Serico Sostenibile Srl Laboratory declines all responsibility.



mailbox@textilecomo.com

via Castelnuovo, 3 - 22100 Como Italia Pho +39 031 3312111/120 Fax: +39 0313312149 Amministrazione/Contabilità +39 031 3312102-154 P. IVA - C.F. 003900470133 Capitale sociale euro 600000,00 iv





LAB N° 0045 L

Test Report No.:	2006501-002		
Test	Method	U.M.	Result
			The Laboratory Manager Fausto Albonico
			The
	END OF	REPORT	

(*) = The tests marked in this way are not accredited by Accredia

The Results contained in this Report refer only to the Sample as received and do not imply an approval of the tested product by the Laboratory of the Centro Tessile Serico Sostenibile Srl. Unless otherwise specified, the side examined / straight of use is indicated by the Customer: this information can influence the results of the tests and therefore the Test Laboratory declines all responsibility.

This Report may not be reproduced in part, unless written permission of Centro Tessile Serico Sostenibile Srl Laboratory.

[C] = Information provided by the Customer, of which the Centro Tessile Serico Sostenibile Srl Laboratory declines all responsibility.



Centro Tessile Serico Sostenibile SrI
Via Castelnuovo, 3 – 22100 Como Italia
Tel. +39 031331211/120 Fax +39 031 3312149
Amministrazione/Contabilità +39 031 3312102-154
P.IVA – C.F. 03900470133
Capitale sociale euro 600.000,00 iv
mailbox@textilecomo.com
www.textilecomo.com





I AR Nº 0045 I

Annex n. 1F to test report n. 2006501-002

DETAILS OF TEST RESULTS

Test executed according to UNI EN 1021-2:2014 (EN 1021-1:2014) Furniture - Assessment of the ignitability of upholstered furniture Part 2: Ignition source: match flame equivalent

Article description: CARNIVAL

Declared composition: 40% Cotton - 22% Acrylic - 16% Viscose - 11% Wool - 11% Polyester

Materials of test assembly:

Upholstery filling: fire-retardant polyurethane foam with a density of 35 kg/m³

Inner cover: -

Outer cover: see article description

Conditioning of test specimen: 23 ± 2 °C, 50 ± 5 % r.h.

Testing temperature and r.h.: 19°C - 57% r.h.

Sample pre-treatment: sample wasn't submitted to any pretreatment because it wasn't chemically treated

with flame retardant Date of test: 02.11.2020

SMOULDERING CRITERIA:	1st test	2nd test	3rd test	Comments
Smouldering criteria:				
Unsafe escalating combustion	NO	NO	NO	
Test assembly consumed	NO	NO	NO	
Smoulders to extremities	NO	NO	NO	Time smouldering: 1st test: 5 s 2nd test: 6 s 3rd test: 6 s
Smoulders through thickness	NO	NO	NO	
Smoulders more than 1 hour	NO	NO	NO	
In final examination, presence of active smouldering	NO	NO	NO	
Flaming criteria:				
Unsafe escalating combustion	NO	NO	NO	Time flaming: 1st test: 2 s 2nd test: 2 s 3rd test: 2 s
Test assembly consumed	NO	NO	NO	
Flames to extremities	NO	NO	NO	
Flames through thickness	NO	NO	NO	
Flames more than 120 s	NO	NO	NO	

YES = criteria observed

NO = criteria not observed

TEST RESULT: SAMPLE PASSES THE TEST - NON IGNITION

The above test results relate only to the ignitability of the combination of materials under the particular conditions of test. They are not intended as a means of assessing the full potential fire hazard of the material in use. The probability that the observation criteria mentioned represent the truth is equal to 95%.

The expanded uncertainty is calculated by multiplying the combined standard uncertainty for a coverage factor K = 2, which for a normal distribution leads to a confidence level of approximately 95%.