

Centro Tessile Serico Sostenibile Srl

mailbox@textilecomo.com www.textilecomo.com

via Castelnuovo, 3 - 22100 Como Italia Pho +39 031 3312111/120 Fax: +39 0313312149 Amministrazione/Contabilità +39 031 3312102-154 P. IVA - C.F. 003900470133 Capitale sociale euro 600000,00 iv





LAB N° 0045 L

Test Report No.: 2206540-001

Date Test Report 23-set-22

Acceptance: **2206540**

Arrival date sample 21-set-22 Start date test 21-set-22

End date test 23-set-22

References:

es:

Sampling Mode: Sampling by Customer *

Customer Code 05485

Dear:

MARIO SIRTORI SPA

via Papa Giovanni XXIII 10

23845 COSTA MASNAGA (LC) Italia

C.a. sig. Sergio Sala Crist

Phone: +39 031 879632

 [C] Item:
 GARLAND CS

 [C] Declared Composition:
 100% Trevira CS

 [C] End use:
 furnishing

 [C] Typology:
 fabric

 Return:
 no requested

Test Results

Test		Method	U.M.	Result	
15066 UPHOLSTERY FURNITURE COMPONENTS: ASSESSMENT OF THE IGNITABILITY BY SMOULDERING CIGARETTE		TB 117:2013		·	
Start date test	22/09/2022				
End date test	23/09/2022				
Instrument: Mini M	lock Up Tester				
Test carried out on				COVER FABRIC	
Pretreatment carried	out			none	
Ignition source				SMOULDERING CIGARETTE	
Materials of test asse	mbly				
Upholstery filling: NO	ON fire retardant polyur	ethane foam with a density of 28 kg/m³			
Inner cover: -					
Outer cover: SEE ART	TICLE DESCRIPTION				
TEST RESULT				PASS	
Deviations from the n	method	·		none	
Annex n.				1F	
Details of the test result	ts related to each specimen	can be seen in the annex of this test report.			

The Results contained in this Report refer only to the Sample as received and do not imply an approval of the tested product by the Laboratory of the Centro Tessile Serico Sostenibile Srl. Unless otherwise specified, the side examined / straight of use is indicated by the Customer: this information can influence the results of the tests and therefore the Test Laboratory declines all responsibility.

^{(*) =} The tests marked in this way are not accredited by Accredia

 $This \ Report \ may \ not \ be \ reproduced \ in \ part, \ unless \ written \ permission \ of \ Centro \ Tessile \ Serico \ Sostenibile \ Srl \ Laboratory.$

[[]C] = Information provided by the Customer, of which the Centro Tessile Serico Sostenibile Srl Laboratory declines all responsibility.



Centro Tessile Serico Sostenibile Srl

mailbox@textilecomo.com

via Castelnuovo, 3 - 22100 Como Italia Pho +39 031 3312111/120 Fax: +39 0313312149 Amministrazione/Contabilità +39 031 3312102-154 P. IVA - C.F. 003900470133 Capitale sociale euro 600000,00 iv





LAB N° 0045 L

Test Report No.:	2206540-001		
Test	Method	U.M.	Result
			The Laboratory Manager Fausto Albonico
		END OF REPORT	

The Results contained in this Report refer only to the Sample as received and do not imply an approval of the tested product by the Laboratory of the Centro Tessile Serico Sostenibile Srl. Unless otherwise specified, the side examined / straight of use is indicated by the Customer: this information can influence the results of the tests and therefore the Test Laboratory declines all responsibility.

^{(*) =} The tests marked in this way are not accredited by Accredia

This Report may not be reproduced in part, unless written permission of Centro Tessile Serico Sostenibile Srl Laboratory.

[C] = Information provided by the Customer, of which the Centro Tessile Serico Sostenibile Srl Laboratory declines all responsibility.



Centro Tessile Serico Sostenibile Srl

Via Castelnuovo, 3 – 22100 Como Italia Tel. +39 031331211 Fax +39 0313312149 Amministrazione/Contabilità +39 0313312102-154 P.IVA – C.F. 03900470133 Capitale sociale euro 600.000,00 iv





mailbox@textilecomo.com www.textilecomo.com

Annex n. 1F to test report n. 2206540-001

DETAILS OF TEST RESULTS

Test executed according to TB 117:2013

Requirements, Test procedure and Apparatus for testing the Smolder Resistance of Materials used in Upholstered Furniture

Sample description: **GARLAND CS**Declared composition: **100% Trevira CS**

Conditioning of test specimen and ignition source (SRM 1196 cigarette): 24 h at 21 \pm 3 °C, <55% r.h.

Testing temperature and r.h.: 18°C, 44% r.h.

Filling specification: NON FIRE-RETARDANT polyurethane foam with a density of 28 kg/m³

Date of test: 23.09.2022

Type of fabric: COVER FABRIC

Specimen number		2	3
Total combustion of the cigarette (YES / NO)	YES	YES	YES
Time of progressive smouldering from placement of the source (min)		31	30
Size of the damage (mm)		18	19
Mock-up test specimen transitions to open flaming (YES / NO)		NO	NO
CIGARETTE TEST RESULT (PASS/FAIL)		PASS	PASS

Cover Fabric Classification (ref. TB 117:2013)

A single mock-up test specimen fails to meet the requirements if any of the following criteria occurs:

- a) The mock-up test specimen continues to smolder after the 45 minute test duration;
- b) A char in any direction more than 45 mm develops on the cover fabric
- c) The mock-up test specimen transitions to open flaming.
- 2. The cover fabric passes the test if three initial mock-up specimens pass the test, i.e., the cigarettes burn their full length and the mock-ups are no longer smoldering.
- 3. If more than one initial specimen fails, the cover fabric fails the test.
- 4. If any one of the three initial specimens fails, repeat the test on additional three specimens.
- 5. If all three additional specimens pass the test, the cover fabric passes the test. If any one of the additional three specimens fails, the cover fabric fails the test.

The following test result relate only to the ignitability of the combination of materials under the particular conditions of test. They are not intended as a means of assessing the full potential fire hazard of the material in use.

Upholstery cover fabrics that fail the cover fabric test described in Section 1 can be used in upholstered furniture if a barrier (interliner) material that passes the test method described in Section 2 is used. When a barrier is required, the barrier material must cover all sides and top of the seating cushion(s). Exceptions: Non-reversible and non-detachable seating cushions do not require the use of the barrier material on the underside of the seating cushion.

The probability that the criteria represent the truth observation is equal to 95%.

The Laboratory Manager Fausto Albanico